

MOTOR DATA SHEET

-

Motor type: **SUDg160L-8(S3-40%)**

Series: For cranes

30-11-2025

ELECTRICAL PARAMETERS																	
U	CONN.	f	ı	D	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Y+Y	50	7	9.5	S3-40%	17.6	690	96.9	-	2.2	-	79.7	81.0	80.0	0.52	0.65	0.72

GENERAL DATA						
Efficiency class	-	Sound pressure level [dB]	72			
Frame size	160	Sound power level [dB]	61			
Number of poles	8	Terminal box position	top			
Starting method	DOL with external starter	Possibility of terminal box rotation	no			
Insulation class	F	Bearing on D-side	6309 2Z			
Frequency converter supply	on demand	Bearing on ND-side	6309 2Z			
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	no			
Cooling method	IC411	Housing - material	cast iron			
Weight (IMB3) [kg]	150	Feet - material	cast iron			
Moment of inertia [kgm2]	0.119	Bearing shields - material	cast iron			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP44	Climatic execution	N			

ENVIRONMENTAL CONDITIONS						
Ambient temperature [°C]	up to +40 Altitude above sea level [m]		up to 1000			
Relative humidity [%]	up to 95					

ACCESSORY						
Number of terminals or cables	3+3	Temperature sensors in bearings	on demand			
Cable glands/inlets	2 + 1	Winding heaters	on demand			
Temperature sensors in winding	3 x PTC	Optional accessories	on demand			

STANDARDS					
IEC 60034-1					

ADDITIONAL INFO						
Rotor voltage [V]	205 Rotor current [A]		21			
Rotor resistance [ohm]	0.233	Additional rotor resistance [ohm]	5.64			

