



## MOTOR DATA SHEET

Motor type: **ExSg132M-6B-3GT4**

Series: **Non sparking**

18-02-2026

ELECTRICAL PARAMETERS																	
<i>U</i>	CONN.	<i>f</i>	<i>P</i>		Duty	<i>I</i>	<i>n</i>	<i>T</i>	<i>TL/T</i>	<i>TB/T</i>	<i>IL/I</i>	Efficiency at load [%]			Power factor at load [-]		
<i>V</i>	-	Hz	<i>kW</i>	<i>HP</i>	-	A	<i>rpm</i>	<i>Nm</i>	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	4	5.5	S1	8.2	960	39.79	2.5	3.5	7	82.8	84.6	84.8	0.63	0.75	0.83

## GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	62
Frame size	132	Sound power level [dB]	73
Number of poles	6	Terminal box position	top
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	63082Z
Frequency converter supply	on demand	Bearing on ND-side	63082Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	yes
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	105	Feet - material	cast iron
Moment of inertia [kgm <sup>2</sup> ]	0.039	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

## ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	from -20 up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

## ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	2	Winding heaters	no
Temperature sensors in winding	on demand	Optional accessories	on demand

## STANDARDS

EN 60079-0, EN 60079-15

## CERTIFICATES

ATEX

## ADDITIONAL INFO

Ex marking	II 3G ExnA IIC T3-T4 Gc	
------------	-------------------------	--