



MOTOR DATA SHEET

Motor type: **ExSg160M-2B-2GT4**

Series: **Increased safety**

18-02-2026

ELECTRICAL PARAMETERS																	
<i>U</i>	CONN.	<i>f</i>	<i>P</i>		Duty	<i>I</i>	<i>n</i>	<i>T</i>	<i>TL/T</i>	<i>TB/T</i>	<i>IL/I</i>	Efficiency at load [%]			Power factor at load [-]		
<i>V</i>	-	Hz	<i>kW</i>	<i>HP</i>	-	A	<i>rpm</i>	<i>Nm</i>	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	6	8.1	S1	10.7	2950	19.4	2.9	3.3	7.7	85.2	87.8	88.7	0.83	0.89	0.91

GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	73
Frame size	160	Sound power level [dB]	84
Number of poles	2	Terminal box position	top
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	63092Z
Frequency converter supply	no	Bearing on ND-side	63092Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	yes
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	112	Feet - material	cast iron
Moment of inertia [kgm ²]	0.047	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	from -20 up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	2	Winding heaters	no
Temperature sensors in winding	on demand	Optional accessories	on demand

STANDARDS

EN 60079-0, EN 60079-15

CERTIFICATES

ATEX

ADDITIONAL INFO

tE heating time up to T4 temperature [s]	7	Ex marking	II 2G Ex eb IIC T4
--	---	------------	--------------------