

MOTOR DATA SHEET

Motor type: (E)cSg200L6A-EP

Series: Flameproof IE1



30-11-2025

	ELECTRICAL PARAMETERS																	
	U	CONN.	f	ŀ	•	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at lo	oad [-]
,	V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
4	00	Y	50	18.5	25	S1	34.5	980	180	2.5	2.4	6.8	90.0	90.8	90.5	0.76	0.83	0.86

GENERAL DATA						
Efficiency class	-	Sound pressure level [dB]	63			
Frame size	200	Sound power level [dB]	75			
Number of poles	6	Terminal box position	top			
Starting method	DOL	Possibility of terminal box rotation	no			
Insulation class	F	Bearing on D-side	NU312			
Frequency converter supply	on request - execution (-f)	Bearing on ND-side	6312C3			
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	yes			
Cooling method	IC411	Housing - material	cast iron			
Weight (IMB3) [kg]	290	Feet - material	cast iron			
Moment of inertia [kgm2]	0.41	Bearing shields - material	cast iron			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP55	Climatic execution	N			

ENVIRONMENTAL CONDITIONS						
Ambient temperature [°C]	from -20 up to +40	Altitude above sea level [m]	up to 1000			
Relative humidity [%]	up to 100					

ACCESSORY							
Number of terminals or cables	3	Temperature sensors in bearings	on demand				
Cable glands/inlets	1	Winding heaters	on demand				
Temperature sensors in winding	on demand	Optional accessories	on demand				

STANDARDS					
IEC 60034-1, IEC 60079-0, IEC 60079-1, IEC 60079-7					

CERTIFICATES
ATEX, EAC, BiH

ADDITIONAL INFO					
Ex marking	II 2G Ex db eb IIC T5 Gb / II 2G Ex db IIB T5 Gb				

