



## MOTOR DATA SHEET

Motor type: **3Sg160M6-(2D,3D)**

Series: **Gas and Dust - category 2D, 3D, 3G**

06-06-2025

### ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	7.5	10	S1	15.3	962	74	2.2	3	6.4	85.3	86.8	87.5	0.61	0.73	0.81

### GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	55
Frame size	160	Sound power level [dB]	65
Number of poles	6	Terminal box position	top
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	63092Z
Frequency converter supply	on demand	Bearing on ND-side	63092Z
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	no
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	146	Feet - material	cast iron
Moment of inertia [kgm <sup>2</sup> ]	0.07	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP66 (2D) / IP56 (3D)	Climatic execution	N

### ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	from -20 up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

### ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	1 x PTC (D-side)
Cable glands/inlets	2 + 1	Winding heaters	on demand
Temperature sensors in winding	3 x PTC	Optional accessories	on demand

### STANDARDS

EN 60034-1, EN 60079-0, EN 60079-15, EN 60079-31

### CERTIFICATES

ATEX

### ADDITIONAL INFO

Ex marking	II 2D,3D Ex t IIIC,IIIB T100°C Db / II 3G ExnA II T5 Gc	
------------	---------------------------------------------------------------	--