

## **MOTOR DATA SHEET**

Motor type: **3SIE100L8B** 

Series: **IE3** 



21-11-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	ı	D	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
230	Δ	50	1.1	1.5	S1	5.4	710	14.8	1.4	2.0	4.0	76.3	78.7	77.7	0.44	0.56	0.66
400	Y	50	1.1	1.5	S1	3.1	710	14.8	1.4	2.0	4.0	76.3	78.7	77.7	0.44	0.56	0.66

GENERAL DATA						
Efficiency class	IE3	Sound pressure level [dB]	53			
Frame size	100	Sound power level [dB]	62			
Number of poles	8	Terminal box position	top			
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes			
Insulation class	F	Bearing on D-side	62062ZC3			
Frequency converter supply	yes	Bearing on ND-side	62062ZC3			
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no			
Cooling method	IC411	Housing - material	aluminium			
Weight (IMB3) [kg]	27	Feet - material	aluminium			
Moment of inertia [kgm2]	0.0122	Bearing shields - material	aluminium			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP55	Climatic execution	N			

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY							
Number of terminals or cables	6	Temperature sensors in bearings	on demand				
Cable glands/inlets	1	Winding heaters	on demand				
Temperature sensors in winding	on demand	Optional accessories	on demand				

STANDARDS
IEC 60034-1

CERTIFICATES	
on demand	

