



# MOTOR DATA SHEET

 Motor type: **3SIE132M2**

 Series: **IE3**


03-02-2026

## ELECTRICAL PARAMETERS

| U   | CONN. | f  | P   |      | Duty | I    | n    | T    | TL/T | TB/T | IL/I | Efficiency at load [%] |      |      | Power factor at load [-] |      |      |
|-----|-------|----|-----|------|------|------|------|------|------|------|------|------------------------|------|------|--------------------------|------|------|
| V   | -     | Hz | kW  | HP   | -    | A    | rpm  | Nm   | -    | -    | -    | 2/4                    | 3/4  | 4/4  | 2/4                      | 3/4  | 4/4  |
| 400 | Δ     | 50 | 9.2 | 12.3 | S1   | 16.6 | 2935 | 29.9 | 3.2  | 3.8  | 9.7  | 90.5                   | 91.2 | 90.7 | 0.74                     | 0.83 | 0.88 |
| 690 | Y     | 50 | 9.2 | 12.3 | S1   | 9.6  | 2935 | 29.9 | 3.2  | 3.8  | 9.7  | 90.5                   | 91.2 | 90.7 | 0.74                     | 0.83 | 0.88 |

## GENERAL DATA

|                                       |                 |                                      |           |
|---------------------------------------|-----------------|--------------------------------------|-----------|
| Efficiency class                      | IE3             | Sound pressure level [dB]            | 68        |
| Frame size                            | 132             | Sound power level [dB]               | 80        |
| Number of poles                       | 2               | Terminal box position                | top       |
| Starting method                       | DOL or Y/Δ      | Possibility of terminal box rotation | yes       |
| Insulation class                      | F               | Bearing on D-side                    | 63082Z    |
| Frequency converter supply            | yes             | Bearing on ND-side                   | 63082Z    |
| Mounting arrangement                  | IMB3/B5/B35/B14 | Bearings regreasing                  | on demand |
| Cooling method                        | IC411           | Housing - material                   | aluminium |
| Weight (IMB3) [kg]                    | 93.0            | Feet - material                      | aluminium |
| Moment of inertia [kgm <sup>2</sup> ] | 0.02            | Bearing shields - material           | cast iron |
| Direction of rotation                 | CW/CCW          | Painting                             | RAL5010   |
| Degree of protection                  | IP55            | Climatic execution                   | N         |

## ENVIRONMENTAL CONDITIONS

|                          |           |                              |            |
|--------------------------|-----------|------------------------------|------------|
| Ambient temperature [°C] | up to +40 | Altitude above sea level [m] | up to 1000 |
| Relative humidity [%]    | up to 95  |                              |            |

## ACCESSORY

|                                |           |                                 |           |
|--------------------------------|-----------|---------------------------------|-----------|
| Number of terminals or cables  | 6         | Temperature sensors in bearings | on demand |
| Cable glands/inlets            | 1         | Winding heaters                 | on demand |
| Temperature sensors in winding | on demand | Optional accessories            | on demand |

## STANDARDS

IEC 60034-1

## CERTIFICATES

on demand