

MOTOR DATA SHEET

Motor type: **3SIE132S8**

Series: **IE3**



21-11-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	,	•	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	2.2	3.0	S1	5.3	710	29.6	2.2	2.9	5.5	81.2	82.6	81.9	0.54	0.66	0.73
690	Y	50	2.2	3.0	S1	3.1	710	29.6	2.2	2.9	5.5	81.2	82.6	81.9	0.54	0.66	0.73

GENERAL DATA							
Efficiency class	IE3	Sound pressure level [dB]	58				
Frame size	132	Sound power level [dB]	67				
Number of poles	8	Terminal box position	top				
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes				
Insulation class	F	Bearing on D-side	63082ZC3				
Frequency converter supply	yes	Bearing on ND-side	63082ZC3				
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	on demand				
Cooling method	IC411	Housing - material	aluminium				
Weight (IMB3) [kg]	46	Feet - material	aluminium				
Bearing shields - material	aluminium	Direction of rotation	CW/CCW				
Painting	RAL5010	Degree of protection	IP55				
Climatic execution	N						

ENVIRONMENTAL CONDITIONS								
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000					
Relative humidity [%]	up to 95							

ACCESSORY							
Number of terminals or cables	6	Temperature sensors in bearings	on demand				
Cable glands/inlets	1	Winding heaters	on demand				
Temperature sensors in winding	on demand	Optional accessories	on demand				

STANDARDS
IEC 60034-1

CERTIFICATES	
on demand	

