



MOTOR DATA SHEET

Motor type: **3SIE160L8**

Series: **IE3**



06-06-2025

ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	7.5	10	S1	16.1	710	100.9	2	2.6	5.4	87.9	88.5	87.3	0.60	0.71	0.77
690	Y	50	7.5	10	S1	9.3	710	100.9	2	2.6	5.4	87.9	88.5	87.3	0.60	0.71	0.77

GENERAL DATA

Efficiency class	IE3	Sound pressure level [dB]	62
Frame size	160	Sound power level [dB]	72
Number of poles	8	Terminal box position	top
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	63092ZC3
Frequency converter supply	yes	Bearing on ND-side	63092ZC3
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	on demand
Cooling method	IC411	Housing - material	aluminium
Weight (IMB3) [kg]	101	Feet - material	aluminium
Moment of inertia [kgm ²]	0.102	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

STANDARDS

IEC 60034-1

CERTIFICATES

on demand