

## **MOTOR DATA SHEET**

Motor type: **3SIE315M6C** 

Series: **IE3** 



21-11-2025

ELECTRICAL PARAMETERS																	
U	CONN.	f	F	•	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	132	175	S1	241	992	1271	2.5	2.5	7.0	95.4	95.8	95.4	0.69	0.78	0.83
690	Y	50	132	175	S1	139	992	1271	2.5	2.5	7.0	95.4	95.8	95.4	0.69	0.78	0.83

GENERAL DATA						
Efficiency class	IE3	Sound pressure level [dB]	70			
Frame size	315	Sound power level [dB]	80			
Number of poles	6	Terminal box position	top			
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes			
Insulation class	F	Bearing on D-side	6320C3			
Frequency converter supply	on demand	Bearing on ND-side	6318C3			
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	yes			
Cooling method	IC411	Housing - material	cast iron			
Weight (IMB3) [kg]	1230	Feet - material	cast iron			
Moment of inertia [kgm2]	4.21	Bearing shields - material	cast iron			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP55	Climatic execution	N			

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY						
Number of terminals or cables	6	Temperature sensors in bearings	on demand			
Cable glands/inlets	2 + 1	Winding heaters	on demand			
Temperature sensors in winding	3 x PTC	Optional accessories	on demand			

STANDARDS	
IEC 60034-1	

CERTIFICATES	
on demand	

