

## MOTOR DATA SHEET

Motor type: **2SIE160M2A**

Series: **IE2**



03-02-2026

ELECTRICAL PARAMETERS																	
<i>U</i>	CONN.	<i>f</i>	<i>P</i>		Duty	<i>I</i>	<i>n</i>	<i>T</i>	<i>TL/T</i>	<i>TB/T</i>	<i>IL/I</i>	Efficiency at load [%]			Power factor at load [-]		
<i>V</i>	-	Hz	<i>kW</i>	<i>HP</i>	-	A	<i>rpm</i>	<i>Nm</i>	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	11	15	S1	20.3	2940	35.73	2.0	2.7	7.2	89.4	90.3	90.0	0.73	0.83	0.87
690	Y	50	11	15	S1	11.8	2940	35.73	2.0	2.7	7.2	89.4	90.3	90.0	0.73	0.83	0.87

## GENERAL DATA

Efficiency class	IE2	Sound pressure level [dB]	70
Frame size	160	Sound power level [dB]	83
Number of poles	2	Terminal box position	top
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	63092Z
Frequency converter supply	yes	Bearing on ND-side	63092Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	on demand
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	96.0	Feet - material	cast iron
Moment of inertia [kgm <sup>2</sup> ]	0.042	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

## ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

## ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

## STANDARDS

IEC 60034-1

## CERTIFICATES

on demand