

## MOTOR DATA SHEET

Motor type: **PSg132M-6**



Series: **IE1**

**IE1** STANDARD EFFICIENCY

03-02-2026

ELECTRICAL PARAMETERS																	
<i>U</i>	CONN.	<i>f</i>	<i>P</i>		Duty	<i>I</i>	<i>n</i>	<i>T</i>	<i>TL/T</i>	<i>TB/T</i>	<i>IL/I</i>	Efficiency at load [%]			Power factor at load [-]		
<i>V</i>	-	Hz	<i>kW</i>	<i>HP</i>	-	A	<i>rpm</i>	<i>Nm</i>	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	7.5	10	S1	16.3	950	75.4	2.5	2.9	6.1	84.5	85.3	84.2	0.59	0.73	0.79
690	Y	50	7.5	10	S1	9.4	950	75.4	2.5	2.9	6.1	84.5	85.3	84.2	0.59	0.73	0.79

### GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	73
Frame size	132	Sound power level [dB]	74
Number of poles	6	Terminal box position	top
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes
Bearing on D-side	6308 2Z C3	Frequency converter supply	yes
Bearing on ND-side	6308 2Z C3	Mounting arrangement	IMB3/B5/B35
Bearings regreasing	on demand	Cooling method	IC411
Housing - material	cast iron	Weight (IMB3) [kg]	78.0
Feet - material	cast iron	Moment of inertia [kgm <sup>2</sup> ]	0.039
Bearing shields - material	cast iron	Direction of rotation	CW/CCW
Painting	RAL5010	Degree of protection	IP55
Climatic execution	N		

### ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

### ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

### STANDARDS

IEC 60034-1

### CERTIFICATES

on demand