



MOTOR DATA SHEET

Motor type: **Sg112M-8**

Series: **IE1**

08-05-2024

ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	N	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	1.5	2.0	S1	4.0	720	19.89	1.9	2.3	4.6	72.5	76.2	76.8	0.48	0.62	0.71
690	Y	50	1.5	2.0	S1	2.3	720	19.89	1.9	2.3	4.6	72.5	76.2	76.8	0.48	0.62	0.71

GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	57
Frame size	112	Sound power level [dB]	67
Number of poles	8	Terminal box position	top
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	63062Z
Frequency converter supply	yes	Bearing on ND-side	63062Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no
Cooling method	IC411	Housing - material	aluminium
Weight (IMB3) [kg]	31	Feet - material	aluminium
Moment of inertia [kgm ²]	0.0192	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

STANDARDS

IEC 60034-1

CERTIFICATES

on demand