

## MOTOR DATA SHEET



Motor type: **Sg180L-8**

Series: **IE1**



03-02-2026

| ELECTRICAL PARAMETERS |       |          |           |           |      |          |            |           |             |             |             |                        |      |      |                          |      |      |
|-----------------------|-------|----------|-----------|-----------|------|----------|------------|-----------|-------------|-------------|-------------|------------------------|------|------|--------------------------|------|------|
| <i>U</i>              | CONN. | <i>f</i> | <i>P</i>  |           | Duty | <i>I</i> | <i>n</i>   | <i>T</i>  | <i>TL/T</i> | <i>TB/T</i> | <i>IL/I</i> | Efficiency at load [%] |      |      | Power factor at load [-] |      |      |
| <i>V</i>              | -     | Hz       | <i>kW</i> | <i>HP</i> | -    | A        | <i>rpm</i> | <i>Nm</i> | -           | -           | -           | 2/4                    | 3/4  | 4/4  | 2/4                      | 3/4  | 4/4  |
| 400                   | Δ     | 50       | 11        | 15        | S1   | 23.5     | 730        | 143.9     | 2.0         | 2.4         | 5.5         | 87.7                   | 89.2 | 89.0 | 0.58                     | 0.70 | 0.76 |
| 690                   | Y     | 50       | 11        | 15        | S1   | 13.6     | 730        | 143.9     | 2.0         | 2.4         | 5.5         | 87.7                   | 89.2 | 89.0 | 0.58                     | 0.70 | 0.76 |

### GENERAL DATA

|                                       |                 |                                      |           |
|---------------------------------------|-----------------|--------------------------------------|-----------|
| Efficiency class                      | -               | Sound pressure level [dB]            | 65        |
| Frame size                            | 180             | Sound power level [dB]               | 76        |
| Number of poles                       | 8               | Terminal box position                | top       |
| Starting method                       | DOL or Y/Δ      | Possibility of terminal box rotation | yes       |
| Insulation class                      | F               | Bearing on D-side                    | 63112Z    |
| Frequency converter supply            | yes             | Bearing on ND-side                   | 63112Z    |
| Mounting arrangement                  | IMB3/B5/B35/B14 | Bearings regreasing                  | on demand |
| Cooling method                        | IC411           | Housing - material                   | cast iron |
| Weight (IMB3) [kg]                    | 165             | Feet - material                      | cast iron |
| Moment of inertia [kgm <sup>2</sup> ] | 0.213           | Bearing shields - material           | cast iron |
| Direction of rotation                 | CW/CCW          | Painting                             | RAL5010   |
| Degree of protection                  | IP55            | Climatic execution                   | N         |

### ENVIRONMENTAL CONDITIONS

|                          |           |                              |            |
|--------------------------|-----------|------------------------------|------------|
| Ambient temperature [°C] | up to +40 | Altitude above sea level [m] | up to 1000 |
| Relative humidity [%]    | up to 95  |                              |            |

### ACCESSORY

|                                |           |                                 |           |
|--------------------------------|-----------|---------------------------------|-----------|
| Number of terminals or cables  | 6         | Temperature sensors in bearings | on demand |
| Cable glands/inlets            | 1         | Winding heaters                 | on demand |
| Temperature sensors in winding | on demand | Optional accessories            | on demand |

### STANDARDS

IEC 60034-1

### CERTIFICATES

on demand