



## MOTOR DATA SHEET

Motor type: **2Sg315M4\_2**

Series: **MULTI SPEED**



17-05-2024

### ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	N	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	95	127	S1	161	1468	640	2.4	3.1	6.8	95.7	95.8	95.5	0.82	0.87	0.89
400	YY	50	115	154	S1	188	2970	370	1.6	2.5	6.2	94.6	95.1	95.0	0.91	0.93	0.93

### GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	67 77
Frame size	315	Sound power level [dB]	77 87
Number of poles	4 2	Terminal box position	on right side
Starting method	DOL or Y/Δ / DOL	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	6318P63E1
Frequency converter supply	on demand	Bearing on ND-side	6318P63E1
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	yes
Cooling method	IC411	Housing - material	cast iron
Weight [kg]	880	Feet - material	cast iron
Moment of inertia [kgm <sup>2</sup> ]	2.27	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

### ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

### ACCESSORY

Number of terminals or cables	9	Temperature sensors in bearings	on demand
Cable glands/inlets	2 + 1	Winding heaters	on demand
Temperature sensors in winding	yes	Optional accessories	on demand

### STANDARDS

IEC 60034-1

### CERTIFICATES

on demand