

MOTOR DATA SHEET

Motor type: 2Sg315M8_6

Series: MULTI SPEED



21-11-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	,	Þ	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Y	50	55	74	S1	105	739	711	3.0	2.3	7.0	90.4	91.3	91.0	0.67	0.77	0.83
400	Y	50	75	100	S1	132	988	725	2.3	2.2	7.1	92.7	93.3	93.2	0.77	0.85	0.88

GENERAL DATA							
Efficiency class	-	Sound pressure level [dB]	-				
Frame size	315	Sound power level [dB]	-				
Number of poles	8 6	Terminal box position	on right side				
Starting method	DOL / DOL	Possibility of terminal box rotation	yes				
Insulation class	F	Bearing on D-side	6318P63E1				
Frequency converter supply	on demand	Bearing on ND-side	6318P63E1				
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	yes				
Cooling method	IC411	Housing - material	cast iron				
Weight (IMB3) [kg]	844	Feet - material	cast iron				
Moment of inertia [kgm2]	2.86	Bearing shields - material	cast iron				
Direction of rotation	CW/CCW	Painting	RAL5010				
Degree of protection	IP55	Climatic execution	N				

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY							
Number of terminals or cables	6	Temperature sensors in bearings	on demand				
Cable glands/inlets	2 + 1	Winding heaters	on demand				
Temperature sensors in winding	yes	Optional accessories	on demand				

STANDARDS
IEC 60034-1

CERTIFICATES	
on demand	

