



MOTOR DATA SHEET

Motor type: **SIE200L8_6B-K**

Series: **MULTI SPEED**



17-05-2024

ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	N	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Y	50	14.5	19.5	S1	35	740	187	2.8	3.1	6.1	78.7	82.9	84.2	0.47	0.61	0.71
400	Y	50	19	25.5	S1	36	982	185	1.6	2.2	5.4	87.3	88.1	87.3	0.75	0.84	0.87

GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	62 61
Frame size	200	Sound power level [dB]	72 71
Number of poles	8 6	Terminal box position	on right side
Starting method	DOL / DOL	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	6312P63E1
Frequency converter supply	on demand	Bearing on ND-side	6312P63E1
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	yes
Cooling method	IC411	Housing - material	cast iron
Weight [kg]	270	Feet - material	cast iron
Moment of inertia [kgm ²]	0.47	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	2 + 1	Winding heaters	on demand
Temperature sensors in winding	yes	Optional accessories	on demand

STANDARDS

IEC 60034-1

CERTIFICATES

on demand