



MOTOR DATA SHEET

Motor type: **SIE225M6_4W-K**

Series: **MULTI SPEED**

24
68
POLES
MULTI
SPEED

03-02-2026

ELECTRICAL PARAMETERS																	
<i>U</i>	CONN.	<i>f</i>	<i>P</i>		Duty	<i>I</i>	<i>n</i>	<i>T</i>	<i>TL/T</i>	<i>TB/T</i>	<i>IL/I</i>	Efficiency at load [%]			Power factor at load [-]		
<i>V</i>	-	Hz	<i>kW</i>	<i>HP</i>	-	A	<i>rpm</i>	<i>Nm</i>	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Y	50	13	17	S1	25	989	126	2.3	2.9	7.7	-	-	88.1	-	-	0.88
400	Y	50	37	50	S1	65	1479	239	1.8	2.6	6.7	-	-	91.7	-	-	0.91

GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	62 71
Frame size	225	Sound power level [dB]	72 81
Number of poles	6 4	Terminal box position	on right side
Starting method	DOL / DOL	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	6313P63E1
Frequency converter supply	on demand	Bearing on ND-side	6313P63E1
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	yes
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	365	Feet - material	cast iron
Moment of inertia [kgm ²]	0.87	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	2 + 1	Winding heaters	on demand
Temperature sensors in winding	yes	Optional accessories	on demand

STANDARDS

IEC 60034-1

CERTIFICATES

on demand