

MOTOR DATA SHEET

Motor type: SIE225S8_4-K



Series: MULTI SPEED

	ELECTRICAL PARAMETERS																
U	CONN.	f	I	D	Duty	I	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	А	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	22	29	S1	47	738	285	2.1	2.3	5.8	88.3	89.2	88.5	-	-	0.77
400	YY	50	32	43	S1	56	1475	207	1.4	2.3	6.2	89.9	90.0	89.0	-	-	0.92

GENERAL DATA						
Efficiency class	-	Sound pressure level [dB]	60 72			
Frame size	225	Sound power level [dB]	70 82			
Number of poles	8 4 Terminal box position		on right side			
Starting method	DOL or Y/Δ / DOL Possibility of terminal box rotation		yes			
Insulation class	F Bearing on D-side		6313P63E1			
Frequency converter supply	on demand	Bearing on ND-side	6313P63E1			
Mounting arrangement	IMB3/B5/B35 Bearings regreasing		yes			
Cooling method	IC411	Housing - material	cast iron			
Weight (IMB3) [kg]	330	Feet - material	cast iron			
Moment of inertia [kgm2]	0.76	Bearing shields - material	cast iron			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP55	Climatic execution	Ν			

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY							
Number of terminals or cables	9	Temperature sensors in bearings	on demand				
Cable glands/inlets	2 + 1	Winding heaters	on demand				
Temperature sensors in winding	yes	Optional accessories	on demand				

STANDARDS
IEC 60034-1

CERTIFICATES

on demand



As part of our development program, we reserve the rights to alter or amend any of the specifications without giving prior notice.

Copyright © 2025 Cantoni Group www.cantonigroup.com