

## **MOTOR DATA SHEET**

Motor type: Sg100L-8\_4A

Series: MULTI SPEED



21-11-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	ŀ	•	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	0.7	0.94	S1	2.8	715	9.35	2.2	2.8	3.6	53.5	60.8	64.2	0.38	0.48	0.57
400	YY	50	1.25	1.7	S1	2.8	1425	8.38	1.7	2.5	5.05	77.5	78.9	77.7	0.68	0.79	0.86

GENERAL DATA						
Efficiency class	-	Sound pressure level [dB]	52 64			
Frame size	100	Sound power level [dB]	68 78			
Number of poles	8 4	Terminal box position	top			
Starting method	DOL / DOL	Possibility of terminal box rotation	yes			
Insulation class	F	Bearing on D-side	62062Z			
Frequency converter supply	on demand	Bearing on ND-side	62062Z			
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no			
Cooling method	IC411	Housing - material	aluminium			
Weight (IMB3) [kg]	23.8	Feet - material	aluminium			
Moment of inertia [kgm2]	0.0088	Bearing shields - material	aluminium			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP 55	Climatic execution	N			

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY							
Number of terminals or cables	6	Temperature sensors in bearings	on demand				
Cable glands/inlets	1	Winding heaters	on demand				
Temperature sensors in winding	on demand	Optional accessories	on demand				

STANDARDS	
IEC 60034-1	

CERTIFICATES	
on demand	

