



MOTOR DATA SHEET

Motor type: **Sg112M-8_6**

Series: **MULTI SPEED**

03-02-2026

24
68
POLES
MULTI
SPEED

| ELECTRICAL PARAMETERS | | | | | | | | | | | | | | | | | |
|-----------------------|-------|----------|-----------|-----------|------|----------|------------|-----------|-------------|-------------|-------------|------------------------|------|------|--------------------------|------|------|
| <i>U</i> | CONN. | <i>f</i> | <i>P</i> | | Duty | <i>I</i> | <i>n</i> | <i>T</i> | <i>TL/T</i> | <i>TB/T</i> | <i>IL/I</i> | Efficiency at load [%] | | | Power factor at load [-] | | |
| <i>V</i> | - | Hz | <i>kW</i> | <i>HP</i> | - | A | <i>rpm</i> | <i>Nm</i> | - | - | - | 2/4 | 3/4 | 4/4 | 2/4 | 3/4 | 4/4 |
| 400 | Y | 50 | 1.2 | 1.6 | S1 | 3.9 | 720 | 15.92 | 2.15 | 2.8 | 4.5 | 62.5 | 68.6 | 70.9 | 0.42 | 0.54 | 0.63 |
| 400 | Y | 50 | 1.6 | 2.1 | S1 | 4.1 | 955 | 16 | 1.5 | 2.0 | 4.8 | 73.5 | 77.4 | 78.1 | 0.51 | 0.64 | 0.73 |

GENERAL DATA

| | | | |
|---------------------------------------|-----------------|--------------------------------------|-----------|
| Efficiency class | - | Sound pressure level [dB] | 64 63 |
| Frame size | 112 | Sound power level [dB] | 67 65 |
| Number of poles | 8 6 | Terminal box position | top |
| Starting method | DOL / DOL | Possibility of terminal box rotation | yes |
| Insulation class | F | Bearing on D-side | 63062Z |
| Frequency converter supply | on demand | Bearing on ND-side | 63062Z |
| Mounting arrangement | IMB3/B5/B35/B14 | Bearings regreasing | no |
| Cooling method | IC411 | Housing - material | aluminium |
| Weight (IMB3) [kg] | 33 | Feet - material | aluminium |
| Moment of inertia [kgm ²] | 0.0178 | Bearing shields - material | cast iron |
| Direction of rotation | CW/CCW | Painting | RAL5010 |
| Degree of protection | IP 55 | Climatic execution | N |

ENVIRONMENTAL CONDITIONS

| | | | |
|--------------------------|-----------|------------------------------|------------|
| Ambient temperature [°C] | up to +40 | Altitude above sea level [m] | up to 1000 |
| Relative humidity [%] | up to 95 | | |

ACCESSORY

| | | | |
|--------------------------------|-----------|---------------------------------|-----------|
| Number of terminals or cables | 6 | Temperature sensors in bearings | on demand |
| Cable glands/inlets | 1 | Winding heaters | on demand |
| Temperature sensors in winding | on demand | Optional accessories | on demand |

STANDARDS

IEC 60034-1

CERTIFICATES

on demand