

## **MOTOR DATA SHEET**

Motor type: Sg180L-6\_4

Series: MULTI SPEED



21-11-2025

ELECTRICAL PARAMETERS																	
U	CONN.	f		Р	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Y	50	8.5	11.40	S1	18.2	985	82.41	2.6	2.8	6.8	80.1	83.5	84.2	0.60	0.73	0.80
400	Y	50	13	17.5	S1	24.7	1470	84.46	2.2	2.3	6.5	82.5	85.1	85.4	0.79	0.86	0.89

GENERAL DATA							
Efficiency class	-	Sound pressure level [dB]	65 65				
Frame size	180	Sound power level [dB]	70 77				
Number of poles	6 4	Terminal box position	top				
Starting method	DOL / DOL	Possibility of terminal box rotation	yes				
Insulation class	F	Bearing on D-side	63112Z				
Frequency converter supply	on demand	Bearing on ND-side	63112Z				
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	on demand				
Cooling method	IC411	Housing - material	cast iron				
Weight (IMB3) [kg]	165	Feet - material	cast iron				
Moment of inertia [kgm2]	0.19	Bearing shields - material	cast iron				
Direction of rotation	CW/CCW	Painting	RAL5010				
Degree of protection	IP 55	Climatic execution	N				

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY							
Number of terminals or cables	6	Temperature sensors in bearings	on demand				
Cable glands/inlets	1	Winding heaters	on demand				
Temperature sensors in winding	on demand	Optional accessories	on demand				

STANDARDS
IEC 60034-1

CERTIFICATES	
on demand	

