



## MOTOR DATA SHEET

 Motor type: **Sh71-6\_4A**

 Series: **MULTI SPEED**

03-02-2026

### ELECTRICAL PARAMETERS

| U   | CONN. | f  | P    |      | Duty | I   | n    | T    | TL/T | TB/T | IL/I | Efficiency at load [%] |     |      | Power factor at load [-] |     |      |
|-----|-------|----|------|------|------|-----|------|------|------|------|------|------------------------|-----|------|--------------------------|-----|------|
| V   | -     | Hz | kW   | HP   | -    | A   | rpm  | Nm   | -    | -    | -    | 2/4                    | 3/4 | 4/4  | 2/4                      | 3/4 | 4/4  |
| 400 | Y     | 50 | 0.06 | 0.08 | S1   | 0.5 | 940  | 0.61 | 1.5  | 1.9  | 2.0  | -                      | -   | 35.0 | -                        | -   | 0.70 |
| 400 | Y     | 50 | 0.18 | 0.24 | S1   | 1.1 | 1400 | 1.23 | 1.5  | 1.9  | 2.2  | -                      | -   | 45.0 | -                        | -   | 0.70 |

### GENERAL DATA

|                                       |                 |                                      |           |
|---------------------------------------|-----------------|--------------------------------------|-----------|
| Efficiency class                      | -               | Sound pressure level [dB]            | -         |
| Frame size                            | 71              | Sound power level [dB]               | -         |
| Number of poles                       | 6 4             | Terminal box position                | top       |
| Starting method                       | DOL / DOL       | Possibility of terminal box rotation | yes       |
| Insulation class                      | F               | Bearing on D-side                    | 62032Z    |
| Frequency converter supply            | on demand       | Bearing on ND-side                   | 62032Z    |
| Mounting arrangement                  | IMB3/B5/B35/B14 | Bearings regreasing                  | no        |
| Cooling method                        | IC411           | Housing - material                   | aluminium |
| Weight (IMB3) [kg]                    | 4.9             | Feet - material                      | aluminium |
| Moment of inertia [kgm <sup>2</sup> ] | 0.000736        | Bearing shields - material           | aluminium |
| Direction of rotation                 | CW/CCW          | Painting                             | RAL5010   |
| Degree of protection                  | IP 54/IP 55     | Climatic execution                   | U/2       |

### ENVIRONMENTAL CONDITIONS

|                          |           |                              |            |
|--------------------------|-----------|------------------------------|------------|
| Ambient temperature [°C] | up to +40 | Altitude above sea level [m] | up to 1000 |
| Relative humidity [%]    | up to 95  |                              |            |

### ACCESSORY

|                               |   |  |  |
|-------------------------------|---|--|--|
| Number of terminals or cables | 6 |  |  |
|-------------------------------|---|--|--|

### STANDARDS

|             |
|-------------|
| IEC 60034-1 |
|-------------|

### CERTIFICATES

|           |
|-----------|
| on demand |
|-----------|