



MOTOR DATA SHEET

 Motor type: **Sh90S-6_4**

 Series: **MULTI SPEED**


06-06-2025

ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Y	50	0.63	0.85	S1	2.2	950	6.33	2.0	2.2	3.7	51.6	59.7	63.7	0.45	0.56	0.67
400	Y	50	0.9	1.21	S1	2.5	1425	6.03	1.55	2.4	4.05	56.7	64.0	66.5	0.53	0.67	0.78

GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	57 62
Frame size	90	Sound power level [dB]	76 66
Number of poles	6 4	Terminal box position	top
Starting method	DOL / DOL	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	62052Z
Frequency converter supply	on demand	Bearing on ND-side	62052Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no
Cooling method	IC411	Housing - material	aluminium
Weight (IMB3) [kg]	15.4	Feet - material	aluminium
Moment of inertia [kgm ²]	0.0025	Bearing shields - material	aluminium
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP 55	Climatic execution	N

ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

STANDARDS

IEC 60034-1

CERTIFICATES

on demand