



MOTOR DATA SHEET

Motor type: **SVf450X10D**

Series: **STANDARD EFFICIENCY**

04-05-2025

ELECTRICAL PARAMETERS

| U | CONN. | f | P | | Duty | I | n | T | TL/T | TB/T | IL/I | Efficiency at load [%] | | | Power factor at load [-] | | |
|------|-------|----|-----|-----|------|------|-----|------|------|------|------|------------------------|-----|------|--------------------------|-----|------|
| V | - | Hz | kW | HP | - | A | rpm | Nm | - | - | - | 2/4 | 3/4 | 4/4 | 2/4 | 3/4 | 4/4 |
| 6000 | Y | 50 | 315 | 430 | S1 | 40.4 | 593 | 5076 | 1.1 | 2.5 | 5.9 | - | - | 93.8 | - | - | 0.80 |

GENERAL DATA

| | | | |
|---------------------------------------|------------|--------------------------------------|-----------------|
| Efficiency class | - | Sound pressure level [dB] | - |
| Frame size | 450 | Sound power level [dB] | - |
| Number of poles | 10 | Terminal box position | side of housing |
| Starting method | DOL | Possibility of terminal box rotation | yes |
| Insulation class | F | Bearing on D-side | 6326C3 |
| Frequency converter supply | on demand | Bearing on ND-side | 7322BTVP |
| Mounting arrangement | IM3011(V1) | Bearings regreasing | yes |
| Cooling method | IC511 | Housing - material | steel |
| Weight (IMB3) [kg] | 3800 | Feet - material | steel |
| Moment of inertia [kgm ²] | 54.5 | Bearing shields - material | steel |
| Direction of rotation | CW/CCW | Painting | RAL5010 |
| Degree of protection | IP54 | Climatic execution | N |

ENVIRONMENTAL CONDITIONS

| | | | |
|--------------------------|--------------------|------------------------------|------------|
| Ambient temperature [°C] | from -20 up to +40 | Altitude above sea level [m] | up to 1000 |
| Relative humidity [%] | up to 95 | | |

ACCESSORY

| | | | |
|--------------------------------|--------------------------|---------------------------------|--------------------------|
| Number of terminals or cables | 3 | Temperature sensors in bearings | 2 x Pt100 (1 pc/bearing) |
| Cable glands/inlets | 1 | Winding heaters | on demand |
| Temperature sensors in winding | 6 x Pt100 (2 pcs./phase) | Optional accessories | on demand |

STANDARDS

IEC60034-1

CERTIFICATES

on demand