



MOTOR DATA SHEET

Motor type: **Sf315Y4**

Series: **STANDARD EFFICIENCY**

04-05-2025

ELECTRICAL PARAMETERS

| U | CONN. | f | P | | Duty | I | n | T | TL/T | TB/T | IL/I | Efficiency at load [%] | | | Power factor at load [-] | | |
|------|-------|----|-----|-----|------|------|------|------|------|------|------|------------------------|-----|------|--------------------------|-----|------|
| V | - | Hz | kW | HP | - | A | rpm | Nm | - | - | - | 2/4 | 3/4 | 4/4 | 2/4 | 3/4 | 4/4 |
| 6000 | Y | 50 | 250 | 340 | S1 | 29.3 | 1485 | 1608 | 1.3 | 2.8 | 6 | - | - | 94.3 | - | - | 0.87 |

GENERAL DATA

| | | | |
|---------------------------------------|------------|--------------------------------------|---------------|
| Efficiency class | - | Sound pressure level [dB] | - |
| Frame size | 315 | Sound power level [dB] | - |
| Number of poles | 4 | Terminal box position | on right side |
| Starting method | DOL | Possibility of terminal box rotation | yes |
| Insulation class | F | Bearing on D-side | 6320MC3 |
| Frequency converter supply | on demand | Bearing on ND-side | NU320EM1 |
| Mounting arrangement | IM1001(B3) | Bearings regreasing | yes |
| Cooling method | IC611 | Housing - material | steel |
| Weight (IMB3) [kg] | 1680 | Feet - material | steel |
| Moment of inertia [kgm ²] | 5.5 | Bearing shields - material | steel |
| Direction of rotation | CW/CCW | Painting | RAL5010 |
| Degree of protection | IP54 | Climatic execution | N |

ENVIRONMENTAL CONDITIONS

| | | | |
|--------------------------|--------------------|------------------------------|------------|
| Ambient temperature [°C] | from -20 up to +40 | Altitude above sea level [m] | up to 1000 |
| Relative humidity [%] | up to 95 | | |

ACCESSORY

| | | | |
|--------------------------------|--------------------------|---------------------------------|--------------------------|
| Number of terminals or cables | 3 | Temperature sensors in bearings | 2 x Pt100 (1 pc/bearing) |
| Cable glands/inlets | 1 | Winding heaters | on demand |
| Temperature sensors in winding | 6 x Pt100 (2 pcs./phase) | Optional accessories | on demand |

STANDARDS

| |
|------------|
| IEC60034-1 |
|------------|

CERTIFICATES

| |
|-----------|
| on demand |
|-----------|