

## MOTOR DATA SHEET

Motor type: **Sh400H6A**

Series: **HIGH EFFICIENCY**



03-02-2026

### ELECTRICAL PARAMETERS

<i>U</i>	CONN.	<i>f</i>	<i>P</i>		Duty	<i>I</i>	<i>n</i>	<i>T</i>	<i>TL/T</i>	<i>TB/T</i>	<i>IL/I</i>	Efficiency at load [%]			Power factor at load [-]		
<i>V</i>	-	Hz	<i>kW</i>	<i>HP</i>	-	A	<i>rpm</i>	<i>Nm</i>	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
6000	Y	50	315	430	S1	39.6	993	3029	1.2	2.3	6.2	-	-	95.6	-	-	0.80

### GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	81
Frame size	400	Sound power level [dB]	-
Number of poles	6	Terminal box position	top/ * side
Starting method	DOL	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	6324MC3
Frequency converter supply	on demand	Bearing on ND-side	6322MC3/*7322BTPV
Mounting arrangement	B3/B35/V1*	Bearings regreasing	yes
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	2930	Feet - material	cast iron
Moment of inertia [kgm <sup>2</sup> ]	12.5	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

### ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	from -20 up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

### ACCESSORY

Number of terminals or cables	3	Temperature sensors in bearings	2 x Pt100 (1 pc/bearing)
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	6 x Pt100 (2 pcs./phase)	Optional accessories	on demand

### STANDARDS

IEC 60034-1

### CERTIFICATES

on demand