

MOTOR DATA SHEET

Motor type: Sh400H6A

Series: **HIGH EFFICIENCY**



21-11-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	ŀ	•	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
6000	Y	50	315	430	S1	39.6	993	3029	1.2	2.3	6.2	-	-	95.6	-	-	0.80

GENERAL DATA					
Efficiency class	-	Sound pressure level [dB]	81		
Frame size	400	Sound power level [dB]	-		
Number of poles	6	Terminal box position	top/ * side		
Starting method	DOL	Possibility of terminal box rotation	yes		
Insulation class	F	Bearing on D-side	6324MC3		
Frequency converter supply	on demand	Bearing on ND-side	6322MC3/*7322BTVP		
Mounting arrangement	B3/B35/V1*	Bearings regreasing	yes		
Cooling method	IC411	Housing - material	cast iron		
Weight (IMB3) [kg]	2930	Feet - material	cast iron		
Moment of inertia [kgm2]	12.5	Bearing shields - material	cast iron		
Direction of rotation	CW/CCW	Painting	RAL5010		
Degree of protection	IP55	Climatic execution	N		

ENVIRONMENTAL CONDITIONS					
Ambient temperature [°C]	from -20 up to +40 Altitude above sea level [m]		up to 1000		
Relative humidity [%]	up to 95				

ACCESSORY					
Number of terminals or cables	3	Temperature sensors in bearings	2 x Pt100 (1 pc/bearing)		
Cable glands/inlets	1	Winding heaters	on demand		
Temperature sensors in winding	6 x Pt100 (2 pcs./phase)	Optional accessories	on demand		

STANDARDS	
IEC 60034-1	

CERTIFICATES				
on de	emand			

