



## MOTOR DATA SHEET

Motor type: **SIE286T4**

Series: **NEMA PREMIUM**

04-05-2025

### ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
460	Δ	60	22	30	cont.	37.5	1780	119.9	3.5	3.9	9.3	91.3	93.0	93.6	0.61	0.73	0.80

### GENERAL DATA

Efficiency class	NEMA PREMIUM	Sound pressure level [dB]	-
Frame size	286	Sound power level [dB]	-
Number of poles	4	Terminal box position	left side
Starting method	DOL, PWS	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	63112ZC3
Frequency converter supply	on demand	Bearing on ND-side	63112ZC3
Mounting arrangement	IMB3/IMB35	Bearings regreasing	no
Cooling method	IC411	Housing - material	cast iron
Weight [Lbs]	441	Feet - material	cast iron
Moment of inertia [Lb-Ft <sup>2</sup> ]	3.84	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

### ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

### ACCESSORY

Number of terminals or cables	12	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

### STANDARDS

NEMA MG-1

### CERTIFICATES

CSA

### ADDITIONAL INFO

NEMA design	A	NEMA code letter	L
-------------	---	------------------	---