

MOTOR DATA SHEET

Motor type: **SIE447TS2B**

Series: **NEMA PREMIUM**



21-11-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	F	•	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
460	Δ	60	186	250	cont.	263	3579	497.6	1.8	2.7	7.3	96.1	96.2	95.8	0.89	0.92	0.93

GENERAL DATA							
Efficiency class	NEMA PREMIUM	Sound pressure level [dB]	93				
Frame size	447	Sound power level [dB]	103				
Number of poles	2	Terminal box position	left side				
Starting method	DOL, PWS	Possibility of terminal box rotation	yes				
Insulation class	F	Bearing on D-side	6315C3				
Frequency converter supply	on demand	Bearing on ND-side	6315C3				
Mounting arrangement	IMB3/IMB35	Bearings regreasing	yes				
Cooling method	IC411	Housing - material	cast iron				
Weight [Lbs]	2271	Feet - material	cast iron				
Moment of inertia [Lb-Ft2]	36.9	Bearing shields - material	cast iron				
Direction of rotation	CW/CCW	Painting	RAL5010				
Degree of protection	IP55	Climatic execution	N				

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY							
Number of terminals or cables	12	Temperature sensors in bearings	on demand				
Cable glands/inlets	2	Winding heaters	on demand				
Temperature sensors in winding	3 x PTC	Optional accessories	on demand				

STANDARDS	
NEMA MG-1	

CERTIFICATES	
CSA	

ADDITIONAL INFO							
NEMA design	В	NEMA code letter	G				

