

MOTOR DATA SHEET

Motor type: **ESg284T-8**

Series: **NEMA EPACT**



04-05-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	ŀ	•	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Powe	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
460		60	7.5	10	cont.	13.4	880		1.65	2.2	5.3	88.4	89.1	88.5			

GENERAL DATA					
Efficiency class	NEMA EPACT Frame size		284		
Number of poles	8	Insulation class	F		
Frequency converter supply	on demand	Cooling method	IC411		
Direction of rotation	CW/CCW	Painting	RAL5010		
Climatic execution	N				

ENVIRONMENTAL CONDITIONS						
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000			
Relative humidity [%]	up to 95					

ACCESSORY					
Optional accessories	on demand				

STANDARDS
NEMA MG-1

CERTIFICATES					
	CSA				

ADDITIONAL INFO						
NEMA code letter	G					

