



## MOTOR DATA SHEET

Motor type: **STe365TS**

Series: **NEMA EPACT**

18-05-2024

### ELECTRICAL PARAMETERS

| U   | CONN. | f  | P  |    | Duty  | I    | n    | T   | TL/T | TB/T | IL/I | Efficiency at load [%] |      |      | Power factor at load [-] |     |     |
|-----|-------|----|----|----|-------|------|------|-----|------|------|------|------------------------|------|------|--------------------------|-----|-----|
| V   | -     | Hz | kW | HP | -     | A    | rpm  | N   | -    | -    | -    | 2/4                    | 3/4  | 4/4  | 2/4                      | 3/4 | 4/4 |
| 460 | Δ     | 60 | 55 | 75 | cont. | 83.5 | 3556 | 150 | 1.75 | 2    | 5.9  | 94.0                   | 94.2 | 93.6 | 86.2                     | 90  | 90  |

### GENERAL DATA

|   |            |                                      |           |
|---|------------|--------------------------------------|-----------|
| Efficiency class                        | NEMA EPACT | Sound pressure level [dB]            | 80        |
| Frame size                              | 365        | Sound power level [dB]               | 90        |
| Number of poles                         | 2          | Terminal box position                | left side |
| Starting method                         | DOL, PWS   | Possibility of terminal box rotation | yes       |
| Insulation class                        | F          | Bearing on D-side                    | 6313C3    |
| Frequency converter supply              | on demand  | Bearing on ND-side                   | 6313C3    |
| Mounting arrangement                    | IMB3/IMB35 | Bearings regreasing                  | yes       |
| Cooling method                          | IC411      | Housing - material                   | cast iron |
| Weight [Lbs]                            | 780        | Feet - material                      | cast iron |
| Moment of inertia [Lb-Ft <sup>2</sup> ] | 6.65       | Bearing shields - material           | cast iron |
| Direction of rotation                   | CW/CCW     | Painting                             | RAL5010   |
| Degree of protection                    | IP55       | Climatic execution                   | N         |

### ENVIRONMENTAL CONDITIONS

|                          |           |                              |            |
|--------------------------|-----------|------------------------------|------------|
| Ambient temperature [°C] | up to +40 | Altitude above sea level [m] | up to 1000 |
| Relative humidity [%]    | up to 95  |                              |            |

### ACCESSORY

|                                |           |                                 |           |
|--------------------------------|-----------|---------------------------------|-----------|
| Number of terminals or cables  | 12        | Temperature sensors in bearings | on demand |
| Cable glands/inlets            | 2         | Winding heaters                 | on demand |
| Temperature sensors in winding | on demand | Optional accessories            | on demand |

### STANDARDS

NEMA MG-1

### CERTIFICATES

CSA

### ADDITIONAL INFO

|             |   |                  |   |
|-------------|---|------------------|---|
| NEMA design | B | NEMA code letter | F |
|-------------|---|------------------|---|