

MOTOR DATA SHEET

Motor type: **ExSg132M-4-2GT3**

Series: INCREASED SAFETY



01-11-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	ı	D	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	7.5	10	S1	14.6	1450	49.4	2.3	2.8	6.4	85.4	86.4	85.9	0.71	0.82	0.86

GENERAL DATA						
Efficiency class	-	Sound pressure level [dB]	64			
Frame size	132	Sound power level [dB]	75			
Number of poles	4	Terminal box position	top			
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes			
Insulation class	F	Bearing on D-side	63082Z			
Frequency converter supply	no	Bearing on ND-side	63082Z			
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	yes			
Cooling method	IC411	Housing - material	cast iron			
Weight (IMB3) [kg]	71	Feet - material	cast iron			
Moment of inertia [kgm2]	0.035	Bearing shields - material	cast iron			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP55	Climatic execution	N			

	ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	from -20 up to +40	Altitude above sea level [m]	up to 1000					
Relative humidity [%]	up to 95							

ACCESSORY						
Number of terminals or cables	6 Temperature sensors in bearings		on demand			
Cable glands/inlets	2	Winding heaters	no			
Temperature sensors in winding	on demand	Optional accessories	on demand			

STANDARDS
EN 60079-0, EN 60079-15

CERTIFICATES	
ATEX	

ADDITIONAL INFO						
tE heating time up to T3 temperature [s]	5	Ex marking	II 2G Ex eb IIC T3			

