

## **MOTOR DATA SHEET**

Motor type: **ExSh90L-4-2GT3** 

Series: INCREASED SAFETY



21-11-2025

							ELECT	RICAL	PARAN	/IETER	S						
U	CONN.	f		Р	Duty	I	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
40	) Y	50	1.5	2	S1	3.7	1415	10.1	2.5	2.7	4.1	72.5	75.6	75.5	0.55	0.68	0.77

GENERAL DATA						
Efficiency class	-	Sound pressure level [dB]	56			
Frame size	90	Sound power level [dB]	66			
Number of poles	4	Terminal box position	top			
Starting method	DOL	Possibility of terminal box rotation	yes			
Insulation class	F	Bearing on D-side	62052Z			
Frequency converter supply	no	Bearing on ND-side	62052Z			
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no			
Cooling method	IC411	Housing - material	aluminium			
Weight (IMB3) [kg]	15.5	Feet - material	aluminium			
Moment of inertia [kgm2]	15.5	Bearing shields - material	aluminium			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP55	Climatic execution	N			

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	from -20 up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY						
Number of terminals or cables	6	Temperature sensors in bearings	on demand			
Cable glands/inlets	2	Winding heaters	no			
Temperature sensors in winding	on demand	Optional accessories	on demand			

STANDARDS
EN 60079-0, EN 60079-15

	CERTIFICATES
Ī	ATEX

	ADDITIONAL INFO							
tE heating time up to T3 temperature [s]	13	Ex marking	II 2G Ex eb IIC T3					

