

MOTOR DATA SHEET

Motor type: **(E)CSg112M4**

Series: **FLAMEPROOF IE1**



01-11-2025

ELECTRICAL PARAMETERS																	
U	CONN.	f	ŀ	D	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Y	50	4	5.5	S1	8.1	1435	26.6	2.6	3	6.3	83.0	85.0	85.1	0.63	0.76	0.84

GENERAL DATA						
Efficiency class	-	Sound pressure level [dB]	62			
Frame size	112	Sound power level [dB]	72			
Number of poles	4	Terminal box position	top			
Starting method	DOL	Possibility of terminal box rotation	no			
Insulation class	F	Bearing on D-side	63062Z			
Frequency converter supply	on request - execution (-f)	Bearing on ND-side	63062Z			
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	no			
Cooling method	IC411	Housing - material	cast iron			
Weight (IMB3) [kg]	70	Feet - material	cast iron			
Moment of inertia [kgm2]	0.0118	Bearing shields - material	cast iron			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP54	Climatic execution	N			

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	from -20 up to +50	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 100						

ACCESSORY						
Number of terminals or cables	3	Temperature sensors in bearings	on demand			
Cable glands/inlets	1	Winding heaters	on demand			
Temperature sensors in winding	on demand	Optional accessories	on demand			

STANDARDS
IEC 60034-1, IEC 60079-0, IEC 60079-1, IEC 60079-7

CERTIFICATES
ATEX, EAC, BiH

ADDITIONAL INFO					
Ex marking	II 2G Ex db eb IIB T5 Gb / II 2G Ex db IIB T5 Gb				

