

MOTOR DATA SHEET

Motor type: (E)CSg(b)80-4B

Series: **FLAMEPROOF IE1**



21-11-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	F	•	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Y	50	0.75	1	S1	2.3	1405	5.1	3.2	3.3	5	68.0	73.0	74.0	0.42	0.54	0.64

GENERAL DATA					
Efficiency class	-	Sound pressure level [dB]	42		
Frame size	80	Sound power level [dB]	52		
Number of poles	4	Terminal box position	top		
Starting method	DOL	Possibility of terminal box rotation	no		
Insulation class	F	Bearing on D-side	62042Z		
Frequency converter supply	on request - execution (-f)	Bearing on ND-side	62042Z		
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	no		
Cooling method	IC411	Housing - material	cast iron		
Weight (IMB3) [kg]	26.7	Feet - material	cast iron		
Moment of inertia [kgm2]	0.0019	Bearing shields - material	cast iron		
Direction of rotation	CW/CCW	Painting	RAL5010		
Degree of protection	IP54	Climatic execution	N		

ENVIRONMENTAL CONDITIONS						
Ambient temperature [°C]	from -20 up to +50	Altitude above sea level [m]	up to 1000			
Relative humidity [%]	up to 100					

ACCESSORY						
Number of terminals or cables	3	Temperature sensors in bearings	on demand			
Cable glands/inlets	1	Winding heaters	on demand			
Temperature sensors in winding	on demand	Optional accessories	on demand			

STANDARDS					
IEC 60034-1, IEC 60079-0, IEC 60079-1, IEC 60079-7					

CERTIFICATES
ATEX, EAC, BiH

ADDITIONAL INFO					
Ex marking	II 2G Ex db eb IIC T5 Gb / II 2G Ex db IIB +H2 T5 Gb				

