

## **MOTOR DATA SHEET**

Motor type: ExSg132S-4-2GT4\_2D

Series: GAS AND DUST - CATEGORY 2D, 3D, 3G



02-11-2025

ELECTRICAL PARAMETERS																	
U	CONN.	f	ı	•	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	3	4	S1	6	1465	19.6	2.3	3	6.5	82.5	85.0	85.5	0.69	0.79	0.85

GENERAL DATA						
Efficiency class	-	Sound pressure level [dB]	64			
Frame size	132	Sound power level [dB]	75			
Number of poles	4	Terminal box position	top			
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes			
Insulation class	F	Bearing on D-side	63082Z			
Frequency converter supply	no	Bearing on ND-side	63082Z			
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	yes			
Cooling method	IC411	Housing - material	cast iron			
Weight (IMB3) [kg]	60	Feet - material	cast iron			
Moment of inertia [kgm2]	0.028	Bearing shields - material	cast iron			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP66	Climatic execution	N			

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	from -20 up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY							
Number of terminals or cables	6 Temperature sensors in bearings		on demand				
Cable glands/inlets	2	Winding heaters	on demand				
Temperature sensors in winding	3 x PTC	Optional accessories	on demand				

STANDARDS
EN 60034-1, EN 60079-0, EN 60079-7, EN 60079-15, EN 60079-31

CERTIFICATES	
ATEX	

ADDITIONAL INFO					
Ex marking	II 2G Ex eb IIC T4 Gb / II 2D Ex tb IIIC T125°C Db				

