

MOTOR DATA SHEET

Motor type: 2SUg250M8B

Series: **GENERAL PURPOSE**



21-11-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	F	•	Duty	I	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Y	50	30	40	S1	66	732	391	-	3.1	-	-	-	89.3	-	-	0.74

GENERAL DATA						
Efficiency class	-	Sound pressure level [dB]	-			
Frame size	250	Sound power level [dB]	-			
Number of poles	8	Terminal box position	top			
Starting method	DOL	Possibility of terminal box rotation	no			
Insulation class	F	Bearing on D-side	6215C3			
Frequency converter supply	on demand	Bearing on ND-side	6215C3			
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	yes			
Cooling method	IC411	Housing - material	cast iron			
Weight (IMB3) [kg]	535	Feet - material	cast iron			
Moment of inertia [kgm2]	1.6	Bearing shields - material	cast iron			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP55	Climatic execution	N			

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY							
Number of terminals or cables	3+3	Temperature sensors in bearings	on demand				
Cable glands/inlets	3	Winding heaters	on demand				
Temperature sensors in winding	3 x PTC	Optional accessories	on demand				

STANDARDS					
IEC 60034-1					

ADDITIONAL INFO							
Rotor voltage [V]	180	Rotor current [A]	105				
Rotor resistance [ohm]	0.0789	Additional rotor resistance [ohm]	0.9897				

