



MOTOR DATA SHEET

Motor type: **SUem400M12B**

Series: **GENERAL PURPOSE**

03-02-2026

ELECTRICAL PARAMETERS																	
<i>U</i>	CONN.	<i>f</i>	<i>P</i>		Duty	<i>I</i>	<i>n</i>	<i>T</i>	<i>TL/T</i>	<i>TB/T</i>	<i>IL/I</i>	Efficiency at load [%]			Power factor at load [-]		
<i>V</i>	-	Hz	<i>kW</i>	<i>HP</i>	-	A	<i>rpm</i>	<i>Nm</i>	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
380	Δ	50	145	195	S1	304	486	2849	-	2.5	-	-	-	92.8	-	-	0.78

GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	-
Frame size	400	Sound power level [dB]	-
Number of poles	12	Terminal box position	on right side
Starting method	DOL	Possibility of terminal box rotation	no
Insulation class	F	Bearing on D-side	NU324EM1
Frequency converter supply	no	Bearing on ND-side	6322C3
Mounting arrangement	IMB3	Bearings regreasing	yes
Cooling method	IC611	Housing - material	cast iron + steel
Weight (IMB3) [kg]	2300	Feet - material	cast iron
Moment of inertia [kgm ²]	29.9	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP44	Climatic execution	N

ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY

Number of terminals or cables	6+3	Temperature sensors in bearings	on demand
Cable glands/inlets	2	Winding heaters	on demand
Temperature sensors in winding	3 x PTC	Optional accessories	on demand

STANDARDS

IEC 60034-1

ADDITIONAL INFO

Rotor voltage [V]	395	Rotor current [A]	221
-------------------	-----	-------------------	-----