



MOTOR DATA SHEET

 Motor type: **Sg355S10A**

 Series: **ABOVE 8-POLES**

03-02-2026

ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ or Y	50	90	125	S1	176	592	1452	1.3	2.1	5.7	92.2	93.0	93.0	0.64	0.76	0.79
690	Δ or Y	50	90	125	S1	102	592	1452	1.3	2.1	5.7	92.2	93.0	93.0	0.64	0.76	0.79

GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	75
Frame size	355	Sound power level [dB]	-
Number of poles	10	Terminal box position	on right side/* on side
Starting method	bezpośredni lub Y/D	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	NU322 EM1/* 6322 C3
Frequency converter supply	on demand	Bearing on ND-side	6322 C3/* 7322 BTVP
Mounting arrangement	IMB3/B35/V1*	Bearings regreasing	yes
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	1250	Feet - material	cast iron
Moment of inertia [kgm ²]	8.2	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP54	Climatic execution	N

ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	2	Winding heaters	on demand
Temperature sensors in winding	3 x PTC	Optional accessories	on demand

STANDARDS

IEC 60034-1

CERTIFICATES

on demand