

MOTOR DATA SHEET

Motor type: **Ex2SIE_56-2B**

Series: **INCREASED SAFETY IE3**



03-02-2026

ELECTRICAL PARAMETERS																	
<i>U</i>	CONN.	<i>f</i>	<i>P</i>		Duty	<i>I</i>	<i>n</i>	<i>T</i>	<i>TL/T</i>	<i>TB/T</i>	<i>IL/I</i>	Efficiency at load [%]			Power factor at load [-]		
<i>V</i>	-	Hz	<i>kW</i>	<i>HP</i>	-	A	<i>rpm</i>	<i>Nm</i>	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Y	50	0.12	0.17	S1	0.4	2750	0.42	2.3	2.3	3.3	-	-	62.0	-	-	0.70

GENERAL DATA

Efficiency class	IE2	Sound pressure level [dB]	-
Frame size	56	Sound power level [dB]	-
Number of poles	2	Terminal box position	top
Starting method	DOL	Possibility of terminal box rotation	no
Insulation class	F	Bearing on D-side	6201 2Z
Frequency converter supply	no	Bearing on ND-side	6201 2Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no
Cooling method	IC411	Housing - material	aluminium
Weight (IMB3) [kg]	3.3	Feet - material	aluminium
Moment of inertia [kgm ²]	-	Bearing shields - material	aluminium
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP66	Climatic execution	NU/2

ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	from -20 up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	no
Cable glands/inlets	2	Winding heaters	no
Temperature sensors in winding	on demand	Optional accessories	no

STANDARDS

PN-EN 60079-7:2016

CERTIFICATES

ATEX

ADDITIONAL INFO

tE heating time up to T3 temperature [s]	38	tE heating time up to T4 temperature [s]	16
Ex marking	Ex II 2 G Ex eb IIC Tx Gb		

As part of our development program, we reserve the rights to alter or amend any of the specifications without giving prior notice.

Copyright © 2026 Cantoni Group www.cantongroup.com