

MOTOR DATA SHEET

Motor type: **Ex3SIE160L6-2GT3**

Series: **INCREASED SAFETY IE3**



03-02-2026

| ELECTRICAL PARAMETERS | | | | | | | | | | | | | | | | | |
|-----------------------|-------|----------|-----------|-----------|------|----------|------------|-----------|-------------|-------------|-------------|------------------------|------|------|--------------------------|-----|------|
| <i>U</i> | CONN. | <i>f</i> | <i>P</i> | | Duty | <i>I</i> | <i>n</i> | <i>T</i> | <i>TL/T</i> | <i>TB/T</i> | <i>IL/I</i> | Efficiency at load [%] | | | Power factor at load [-] | | |
| <i>V</i> | - | Hz | <i>kW</i> | <i>HP</i> | - | A | <i>rpm</i> | <i>Nm</i> | - | - | - | 2/4 | 3/4 | 4/4 | 2/4 | 3/4 | 4/4 |
| 400 | Δ | 50 | 11 | 15 | S1 | 22 | 970 | 108.3 | 2.2 | 3.0 | 6.8 | 91.0 | 91.0 | 90.3 | | | 0.80 |

GENERAL DATA

| | | | |
|---------------------------------------|-----------------|--------------------------------------|-----------|
| Efficiency class | IE3 | Sound pressure level [dB] | 61 |
| Frame size | 160 | Sound power level [dB] | 74 |
| Number of poles | 6 | Terminal box position | top |
| Starting method | DOL | Possibility of terminal box rotation | yes |
| Insulation class | F | Bearing on D-side | 63092Z |
| Frequency converter supply | yes | Bearing on ND-side | 63092Z |
| Mounting arrangement | IMB3/B5/B35/B14 | Bearings regreasing | no |
| Cooling method | IC411 | Housing - material | aluminium |
| Weight (IMB3) [kg] | 114 | Feet - material | aluminium |
| Moment of inertia [kgm ²] | 0.123 | Bearing shields - material | cast iron |
| Direction of rotation | CW/CCW | Painting | RAL5010 |
| Degree of protection | IP55 | Climatic execution | N |

ENVIRONMENTAL CONDITIONS

| | | | |
|--------------------------|--------------------|------------------------------|------------|
| Ambient temperature [°C] | from -20 up to +40 | Altitude above sea level [m] | up to 1000 |
| Relative humidity [%] | up to 95 | | |

ACCESSORY

| | | | |
|--------------------------------|-----------|---------------------------------|-----------|
| Number of terminals or cables | 6 | Temperature sensors in bearings | on demand |
| Cable glands/inlets | 2 | Winding heaters | no |
| Temperature sensors in winding | on demand | Optional accessories | on demand |

STANDARDS

EN 60034-1, EN-IEC 60079-0, EN 60079-7

CERTIFICATES

ATEX

ADDITIONAL INFO

| | | | |
|--|----|------------|--------------------|
| tE heating time up to T3 temperature [s] | 14 | Ex marking | II 2G Ex eb IIC T3 |
|--|----|------------|--------------------|