



MOTOR DATA SHEET

Motor type: **SEh56-4C**

Series: **SINGLE PHASE**

03-02-2026

ELECTRICAL PARAMETERS

| <i>U</i> | CONN. | <i>f</i> | <i>P</i> | | Duty | <i>I</i> | <i>n</i> | <i>T</i> | <i>TL/T</i> | <i>TB/T</i> | <i>IL/I</i> | Efficiency at load [%] | | | Power factor at load [-] | | |
|----------|-------|----------|-----------|-----------|------|----------|------------|-----------|-------------|-------------|-------------|------------------------|-----|------|--------------------------|-----|------|
| <i>V</i> | - | Hz | <i>kW</i> | <i>HP</i> | - | A | <i>rpm</i> | <i>Nm</i> | - | - | - | 2/4 | 3/4 | 4/4 | 2/4 | 3/4 | 4/4 |
| 230 | - | 50 | 0.12 | 0.17 | S1 | 1.2 | 1400 | 0.81 | 0.5 | 1.5 | 2 | - | - | 50.0 | - | - | 0.86 |

GENERAL DATA

| | | | |
|---------------------------------------|-----------------|--------------------------------------|-----------|
| Efficiency class | - | Sound pressure level [dB] | - |
| Frame size | 56 | Sound power level [dB] | - |
| Number of poles | 4 | Terminal box position | top |
| Starting method | DOL | Possibility of terminal box rotation | yes |
| Insulation class | F | Bearing on D-side | 62012Z |
| Frequency converter supply | - | Bearing on ND-side | 62012Z |
| Mounting arrangement | IMB3/B5/B35/B14 | Bearings regreasing | no |
| Cooling method | IC411 | Housing - material | aluminium |
| Weight (IMB3) [kg] | 3.4 | Feet - material | aluminium |
| Moment of inertia [kgm ²] | 0.0003 | Bearing shields - material | aluminium |
| Direction of rotation | CW/CCW | Painting | RAL5010 |
| Degree of protection | IP 54/IP 55 | Climatic execution | U/2 |

ENVIRONMENTAL CONDITIONS

| | | | |
|--------------------------|--------------------|------------------------------|------------|
| Ambient temperature [°C] | from -15 up to +40 | Altitude above sea level [m] | up to 1000 |
| Relative humidity [%] | up to 95 | | |

ACCESSORY

| | | | |
|--------------------------------|----|---------------------------------|-----------|
| Number of terminals or cables | 4 | Temperature sensors in bearings | no |
| Cable glands/inlets | 1 | Winding heaters | no |
| Temperature sensors in winding | no | Optional accessories | on demand |

STANDARDS

IEC 60034-1

CERTIFICATES

on demand

ADDITIONAL INFO

| | | | |
|--------------------------|---|-------------------------------|---|
| Run capacitor [mikroF/V] | 5 | Starting capacitor [mikroF/V] | - |
|--------------------------|---|-------------------------------|---|