



MOTOR DATA SHEET

Motor type: **2SIE355H4E**

Series: **IE2**

23-05-2025

ELECTRICAL PARAMETERS

| U | CONN. | f | P | | Duty | I | n | T | TL/T | TB/T | IL/I | Efficiency at load [%] | | | Power factor at load [-] | | |
|-----|--------|----|-----|-----|------|-----|------|------|------|------|------|------------------------|------|------|--------------------------|------|------|
| V | - | Hz | kW | HP | - | A | rpm | Nm | - | - | - | 2/4 | 3/4 | 4/4 | 2/4 | 3/4 | 4/4 |
| 400 | Δ or Y | 50 | 375 | 503 | S1 | 641 | 1488 | 2407 | 1.9 | 2.4 | 7.5 | 95.5 | 95.9 | 95.9 | 0.79 | 0.86 | 0.88 |
| 690 | Δ or Y | 50 | 375 | 503 | S1 | 370 | 1488 | 2407 | 1.9 | 2.4 | 7.5 | 95.5 | 95.9 | 95.9 | 0.79 | 0.86 | 0.88 |

GENERAL DATA

| | | | |
|---------------------------------------|------------------------|--------------------------------------|-------------|
| Efficiency class | IE2 | Sound pressure level [dB] | 84 |
| Frame size | 355 | Sound power level [dB] | - |
| Number of poles | 4 | Terminal box position | top/ * side |
| Starting method | DOL, Y/Δ or VSD | Possibility of terminal box rotation | yes |
| Insulation class | F | Bearing on D-side | 6322 C3 |
| Frequency converter supply | yes | Bearing on ND-side | 6322 C3 |
| Mounting arrangement | IMB3/B35/V1* | Bearings regreasing | yes |
| Cooling method | IC411 | Housing - material | cast iron |
| Weight (IMB3) [kg] | 2450 | Feet - material | cast iron |
| Moment of inertia [kgm ²] | 9.1 | Bearing shields - material | cast iron |
| Direction of rotation | according to the order | Painting | RAL5010 |
| Degree of protection | IP55 | Climatic execution | N |

ENVIRONMENTAL CONDITIONS

| | | | |
|--------------------------|-----------|------------------------------|------------|
| Ambient temperature [°C] | up to +40 | Altitude above sea level [m] | up to 1000 |
| Relative humidity [%] | up to 95 | | |

ACCESSORY

| | | | |
|--------------------------------|-------------------------|---------------------------------|--------------------------|
| Number of terminals or cables | 6 | Temperature sensors in bearings | 2 x Pt100 (1 pc/bearing) |
| Cable glands/inlets | 2 | Winding heaters | on demand |
| Temperature sensors in winding | 6 x Pt100 (2pcs./phase) | Optional accessories | on demand |

STANDARDS

IEC 60034-1

CERTIFICATES

on demand