

MOTOR DATA SHEET

Motor type: Sh355H4B

Series: High efficiency



04-11-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	ŀ	•	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
6000	Y	50	200	270	S1	23.9	1488	1284	1.2	2.4	6	-	-	95.8	-	-	0.84

GENERAL DATA						
Efficiency class	-	Sound pressure level [dB]	82			
Frame size	355	Sound power level [dB]	-			
Number of poles	4	Terminal box position	top/ * side			
Starting method	DOL	Possibility of terminal box rotation	yes			
Insulation class	F	Bearing on D-side	6322MC3			
Frequency converter supply	on demand	Bearing on ND-side	6322MC3			
Mounting arrangement	B3/B35/V1*	Bearings regreasing	yes			
Cooling method	IC411	Housing - material	cast iron			
Weight (IMB3) [kg]	2060	Feet - material	cast iron			
Moment of inertia [kgm2]	5	Bearing shields - material	cast iron			
Direction of rotation	CW or CCW (according to the order)	Painting	RAL5010			
Degree of protection	IP55	Climatic execution	N			

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	from -20 up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY							
Number of terminals or cables	3	Temperature sensors in bearings	2 x Pt100 (1 pc/bearing)				
Cable glands/inlets	1	Winding heaters	on demand				
Temperature sensors in winding	6 x Pt100 (2 pcs./phase)	Optional accessories	on demand				

STANDARDS	
IEC 60034-1	

CERTIFICATES					
on demand					

