

MOTOR DATA SHEET

Motor type: **Sh400H10Bs**

Series: **ABOVE 8-POLES**



03-11-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	F	•	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ or Y	50	250	340	S1	477	593	4026	1.1	2.4	5.6	94.3	94.6	94.6	0.64	0.75	0.80
690	Δ or Y	50	250	340	S1	275	593	4026	1.1	2.4	5.6	94.3	94.6	94.6	0.64	0.75	0.80

GENERAL DATA						
Efficiency class	-	Sound pressure level [dB]	76			
Frame size	400	Sound power level [dB]	-			
Number of poles	10	Terminal box position	top/ * side			
Starting method	bezpośredni. Y/D lub VSD	Possibility of terminal box rotation	yes			
Insulation class	F	Bearing on D-side	6324 C3			
Frequency converter supply	yes	Bearing on ND-side	6322 C3/* 7322 BTVP			
Mounting arrangement	IMB3/B35/V1*	Bearings regreasing	yes			
Cooling method	IC411	Housing - material	cast iron			
Weight (IMB3) [kg]	3170	Feet - material	cast iron			
Moment of inertia [kgm2]	28.5	Bearing shields - material	cast iron			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP55	Climatic execution	N			

ENVIRONMENTAL CONDITIONS						
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000			
Relative humidity [%]	up to 95					

ACCESSORY						
Number of terminals or cables	6	Temperature sensors in bearings	2 x Pt100 (1 pc/bearing)			
Cable glands/inlets	2	Winding heaters	on demand			
Temperature sensors in winding	6 x Pt100 (2pcs./phase)	Optional accessories	on demand			

STANDARDS	
IEC 60034-1	

CERTIFICATES	
on demand	

