

## **MOTOR DATA SHEET**

Motor type: **Sh450H10As** 

Series: **ABOVE 8-POLES** 



03-11-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	F	•	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
690	Δ or Y	50	355	480	S1	392	595	5698	0.8	2.1	6.0	94.3	94.9	94.8	0.63	0.75	0.80

GENERAL DATA						
Efficiency class	-	Sound pressure level [dB]	78			
Frame size	450	Sound power level [dB]	-			
Number of poles	10	Terminal box position	top/ * side			
Starting method	direct or VSD	Possibility of terminal box rotation	yes			
Insulation class	F	Bearing on D-side	6324 C3			
Frequency converter supply	yes	Bearing on ND-side	NU222 /* 7322 BTVP			
Mounting arrangement	IMB3/B35/V1*	Bearings regreasing	yes			
Cooling method	IC411	Housing - material	cast iron			
Weight (IMB3) [kg]	3850	Feet - material	cast iron			
Moment of inertia [kgm2]	39.0	Bearing shields - material	cast iron			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP55	Climatic execution	N			

ENVIRONMENTAL CONDITIONS						
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000			
Relative humidity [%]	up to 95					

ACCESSORY						
Number of terminals or cables	3	Temperature sensors in bearings	2 x Pt100 (1 pc/bearing)			
Cable glands/inlets	3	Winding heaters	on demand			
Temperature sensors in winding	6 x Pt100 (2pcs./phase)	Optional accessories	on demand			

STANDARDS	
IEC 60034-1	

CERTIFICATES					
on demand					

