

MOTOR DATA SHEET



19-04-2024

Motor type: 3SIE132M2A

Series: IE3

	ELECTRICAL PARAMETERS																
U	CONN.	f	I	P	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	А	rpm	N	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	11	15	S1	19.6	2925	35.9	2.6	3.8	8.1	91.3	91.9	91.2	0.79	0.86	0.89
690	Y	50	11	15	S1	11.3	2925	35.9	2.6	3.8	8.1	91.3	91.9	91.2	0.79	0.86	0.89

GENERAL DATA						
Efficiency class	IE3	Sound pressure level [dB]	68			
Frame size	132	Sound power level [dB]	80			
Number of poles	2 Terminal box position		top			
Starting method	DOL or Y/Δ Possibility of terminal box rotation		yes			
Insulation class	F Bearing on D-side		63082Z			
Frequency converter supply	yes	Bearing on ND-side	63082Z			
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	on demand			
Cooling method	IC411	Housing - material	aluminium			
Weight (IMB3) [kg]	96.0	Feet - material	aluminium			
Moment of inertia [kgm2]	0.021	Bearing shields - material	cast iron			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP55	Climatic execution	Ν			

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY						
Number of terminals or cables	6	Temperature sensors in bearings	on demand			
Cable glands/inlets	1	Winding heaters	on demand			
Temperature sensors in winding	on demand	Optional accessories	on demand			

STANDARDS
IEC 60034-1

CERTIFICATES

on demand



As part of our development program, we reserve the rights to alter or amend any of the specifications without giving prior notice.

Copyright © 2024 Cantoni Group www.cantonigroup.com