

## MOTOR DATA SHEET

Motor type: **3SIE132S4**

Series: **IE3**



26-04-2024

### ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	N	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	5.5	7.5	S1	10.4	1465	35.9	2.5	3.4	8.5	88.6	89.8	89.6	0.68	0.78	0.85
690	Y	50	5.5	7.5	S1	6.0	1465	35.9	2.5	3.4	8.5	88.6	89.8	89.6	0.68	0.78	0.85

### GENERAL DATA

Efficiency class	IE3	Sound pressure level [dB]	59
Frame size	132	Sound power level [dB]	72
Number of poles	4	Terminal box position	top
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	63082Z
Frequency converter supply	yes	Bearing on ND-side	63082Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	on demand
Cooling method	IC411	Housing - material	aluminium
Weight (IMB3) [kg]	63	Feet - material	aluminium
Moment of inertia [kgm <sup>2</sup> ]	0.036	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

### ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

### ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

### STANDARDS

IEC 60034-1

### CERTIFICATES

on demand