



## MOTOR DATA SHEET

Motor type: **3SIE132S6**

Series: **IE3**

22-02-2020

### ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
			kW	HP								-	-	-	2/4	3/4	4/4
400	Δ	50	3.0	4.0	S1	6.2	965	29.7	2.2	2.9	6.6	85.4	86.4	85.6	0.62	0.75	0.81
690	Y	50	3.0	4.0	S1	3.6	965	29.7	2.2	2.9	6.6	85.4	86.4	85.6	0.62	0.75	0.81

### GENERAL DATA

Efficiency class	IE3	Sound pressure level [dB]	55
Frame size	132	Sound power level [dB]	67
Number of poles	6	Terminal box position	top
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	6308C3
Frequency converter supply	yes	Bearing on ND-side	6308C3
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no
Cooling method	IC411	Housing - material	aluminium
Weight (IMB3) [kg]	54	Feet - material	aluminium
Moment of inertia [kgm <sup>2</sup> ]	0.044	Bearing shields - material	aluminium
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

### ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

### ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

### STANDARDS

IEC 60034-1

### CERTIFICATES

on demand